Technical specifications
Datasheet, edition October 2026

1140 x 1140 mm · CP3/CP9 FORMAT

CP9 pallet 1140 x 1140 x 150 open deck 6 runners medium

MEDIUM | Open deck | 6 runners

TOP



BOTTOM



5,000 kg	1,500 kg	300 kg
Static load on a flat floor	Dynamic load by forklift or pallet truck	Racking load in pallet racking

DIMENSIONS AND WEIGHT

Item number	QP1140MB6R-PAS-CP9
Length	1140 mm
Width	1140 mm
Height	150 mm
Weight	14.3 kg

CONSTRUCTION AND MATERIAL

Top deck	Open deck
Bottom	6 runners
Load class	Medium
Nestable	No
Material	Nearly 100% recycled plastic (HDPE/PP)
Colour	Black (standard), other colours on request
ISPM 15	Exempt (no treatment needed)


DELIVERY AND DOCUMENTATION

Ordering in stacks	17 pallets per stack (stack height approx. 2550 mm)

1140 x 1140 mm · CP3/CP9 FORMAT

CP9 pallet 1140 x 1140 x 150 open deck 6 runners medium

TECHNICAL DRAWING



Top view and side views, dimensions in mm.

TEST CONDITIONS AND TOLERANCES

- The racking load is determined in a test with 25 kg bags on a conventional pallet racking system.
- Dimensional tolerance of the pallet: +5 / -5 mm. Weight tolerance: +5 / -5 %.
- We test our pallets with an evenly distributed, stable and homogeneous load of bagged goods, for a predetermined period at an ambient temperature of 20 °C. Different load conditions may lead to different results and must be assessed separately.