Q-PALL PLASTIC PALLETS

Technical specifications
Datasheet, edition October 2026

1200 x 1000 mm · INDUSTRIAL PALLET

Plastic pallet 1200 x 1000 x 150 open deck 9 feet light – 2.QP1210LB9FR

LIGHT | Open deck | 9 feet | Nestable

TOP



BOTTOM



2,500 kg	1,000 kg	–
Static load on a flat floor	Dynamic load by forklift or pallet truck	Racking load Not for racking

DIMENSIONS AND WEIGHT

Item number	2.QP1210LB9FR
Length	1200 mm
Width	1000 mm
Height	150 mm
Weight	6.8 kg

CONSTRUCTION AND MATERIAL

Top deck	Open deck
Bottom	9 feet
Load class	Light
Nestable	Yes
Material	Nearly 100% recycled plastic (HDPE/PP/LDPE)
Colour	Black (standard), other colours on request
ISPM 15	Exempt (no treatment needed)

DELIVERY AND DOCUMENTATION

PPWR (EU 2025/40)	Declaration of conformity available
Ordering in stacks	45 pallets per stack (stack dimensions approx. 1200 x 1000 x 2360 mm)

SIMILAR VERSIONS


ITEM NUMBER	DIMENSIONS (MM)	WEIGHT	STATIC	DYNAMIC	RACKING
2.QP1210LB9FR This datasheet	1200 x 1000 x 150	6.8 kg	2,500 kg	1,000 kg	–
1.QP1210LB9FR	1200 x 1000 x 150	6.8 kg	2,500 kg	1,000 kg	–
QP1210LB9FR	1200 x 1000 x 150	6.8 kg	2,500 kg	1,000 kg	–

Click an item number for the page and datasheet of that version. We deliver from a factory where your pallet is available, as close to you as possible. Small differences in height, weight and load capacity between the versions are possible.

1200 x 1000 mm · INDUSTRIAL PALLET

Plastic pallet 1200 x 1000 x 150 open deck 9 feet light – 2.QP1210LB9FR

TECHNICAL DRAWING



Top view and side views, dimensions in mm.

TEST CONDITIONS AND TOLERANCES

- Dimensional tolerance of the pallet: +5 / -5 mm. Weight tolerance: +5 / -5 %.
- We test our pallets with an evenly distributed, stable and homogeneous load of bagged goods, for a predetermined period at an ambient temperature of 20 °C. Different load conditions may lead to different results and must be assessed separately.