Q-PALL PLASTIC PALLETS

Technical specifications
Datasheet, edition October 2026

600 x 800 mm · HALF EURO PALLET

Display pallet 600 x 800 x 145 open deck 3 runners light

LIGHT | Open deck | 3 runners | Nestable

TOP



BOTTOM



500 kg	350 kg	–
Static load on a flat floor	Dynamic load by forklift or pallet truck	Racking load Not for racking

DIMENSIONS AND WEIGHT

Item number	QP6080LR3RR
Length	800 mm
Width	600 mm
Height	145 mm
Weight	2.7 kg

CONSTRUCTION AND MATERIAL

Top deck	Open deck
Bottom	3 runners
Load class	Light
Nestable	Yes
Material	Nearly 100% recycled plastic (HDPE/PP/LDPE)
Colour	Black (standard), other colours on request
ISPM 15	Exempt (no treatment needed)


DELIVERY AND DOCUMENTATION

Pack size	100 pieces
Ordering in stacks	100 pallets per stack (stack dimensions approx. 1200 x 800 x 2320 mm)
PPWR (EU 2025/40)	Declaration of conformity available

600 x 800 mm · HALF EURO PALLET

Display pallet 600 x 800 x 145 open deck 3 runners light

TECHNICAL DRAWING



Top view and side views, dimensions in mm.

TEST CONDITIONS AND TOLERANCES

- Dimensional tolerance of the pallet: +5 / -5 mm. Weight tolerance: +5 / -5 %.
- We test our pallets with an evenly distributed, stable and homogeneous load of bagged goods, for a predetermined period at an ambient temperature of 20 °C. Different load conditions may lead to different results and must be assessed separately.