Q-PALL PLASTIC PALLETS


**Technical specifications**
Datasheet, edition October 2026

1200 x 1000 mm · INDUSTRIAL PALLET


# Hygienic pallet 1200 x 1000 x 160 closed deck 3 runners heavy, racking 2,000 kg

HEAVY | Closed deck | 3 runners

TOP



BOTTOM



| 7,500 kg | 1,500 kg | 2,000 kg |
|---|---|---|
| Static load on a flat floor | Dynamic load by forklift or pallet truck | Racking load in pallet racking |

## DIMENSIONS AND WEIGHT

| | |
|---|---|
| Item number | QPH1210HP3R-CDG |
| Length | 1200 mm |
| Width | 1000 mm |
| Height | 160 mm |
| Weight | 21.5 kg |

## CONSTRUCTION AND MATERIAL

| | |
|---|---|
| Top deck | Closed deck |
| Bottom | 3 runners |
| Load class | Heavy |
| Nestable | No |
| Material | Virgin plastic |
| Colour | Grey |
| ISPM 15 | Exempt (no treatment needed) |


## DELIVERY AND DOCUMENTATION

| | |
|---|---|
| Ordering in stacks | 15 pallets per stack (stack dimensions approx. 1200 x 1000 x 2400 mm) |

1200 x 1000 mm · INDUSTRIAL PALLET

# Hygienic pallet 1200 x 1000 x 160 closed deck 3 runners heavy, racking 2,000 kg

## TECHNICAL DRAWING




Side views, dimensions in mm.

## TEST CONDITIONS AND TOLERANCES

- The racking load is determined in a test with 25 kg bags on a conventional pallet racking system.
- Dimensional tolerance of the pallet: +5 / -5 mm. Weight tolerance: +5 / -5 %.
- We test our pallets with an evenly distributed, stable and homogeneous load of bagged goods, for a predetermined period at an ambient temperature of 20 °C. Different load conditions may lead to different results and must be assessed separately.